

## PRODUCT SPECIFICATIONS

### #235 CHLOR-CLEAN LF

**Description:** #235 Chlor-Clean LF is a general purpose low-foaming formula designed for use in CIP and spray cleaning applications in food processing facilities.

#235 effectively removes protein, fat and carbohydrate deposits while leaving substrates residue free, stainless steel surfaces, clean and bright. At 1-2% concentrations

#235 has a foam collapse of less than 10 seconds.

<b>Physical Properties:</b>	Type--	Water/ Chlorine/Alkali
	Color--	Water white-Pale yellow
	Specific Gravity-	1.15±0.02
	Weight(Density)-	9.59 ppg.±0.2
	Flash Point-	>None
	Foam-	None-Low
	pH (neat)-	9.5 ± 0.5
	Chlorine--	@ 3%

#### **Application:**

CIP & Spray Cleaning- Rinse tank or line with water  
Circulate or spray #235 @ 1/2 -1 oz. per gallon  
at 140° - 150° F. for 25-40 minutes.

HTST units will require 1-2 oz./gallon at 170° -180°  
for 30-60 minutes.

Egg Washing-1/3 -1/2 oz./gallon at 95°-110° F. Maintain  
solution carefully, replace solution every 3-4 hours.

**Note:** U.S.D.A. approved.